

ZA35 Renoster Front-end Loader

Dimensions (mm):


Overall Length 6980mm Overall Width 2300mm Overall Height 3080mm Bucket Width 2440mm

Head Office Wallmannsthal Offramp N1 North, Pretoria Office: +27 (0) 12 548 0263 Office: +27 (0) 12 004 2000 Email: sales@wuhlf.co.za Website: www.wuhlf.co.za Key Features

Bucket Size 2.0m³ Engine Type: YC6108G • Rated Power: 92 kW Operating Weight: 9800kg • Tyre Size: 17.5 - 25 • Permanent 4x4 *Quality without compromise*

ZA35 Renoster Front End Loader

Technical Data:



Specifications	Rated Load Bucket Capacity Raising Time Max Breaking Force Max Drawing Force Max Climbing Gradient Min Turn Radius	3.5 Ton 2.0m³ 5.4s 115kn 90kn 30° 5900mm
Traveling Speed	1st Gear 2nd Gear 3rd Gear 4th Gear Reverse 1str Reverse 2nd	0 - 8km/h 0 - 15.5km/h 0 - 25km/h 0 - 36km/h 0 - 10 km/h 0 - 27km/h
Engine	Rated Power Rated Speed Model	92kW 2200rpm YC6108G
Tyres	Standard Size Front Pressure Rear Pressure	17.5—25 0.343mpa 0.294mpa
Tank Capacities	Fuel Tank Hydraulic Oil Tank Engine Oil Gear Box Axle and Final Reducer Brake System	130 { 115 { 20 { 45 { 28 { 45 {
Axle and Main Transmission	Type Reducer Ratio Final Reducer	Single Stage 5.286 Single Stage Planetary
Transmission	Type Torque Coefficient Main Valve Pressure starts Flow Valve Pressure starts Flux	Power shift transmission 3.23 1.20 –1.40mpa 0.50—0.60mpa 82ℓ / min
Articulation	Type Steering angle	Full Hydraulic articulated frame steering 35°
Working Hydraulics	System Type Working System Pressure Bucket Delivery Time	35 Open Mode Controlling 16mpa 1.1s
Brake System	Brake Pressure Foot brake Type	0.45 - 0.68mpa Air assisted